



Electrical Information	
Model No.	SL-DL7001-30W
Power Consumption(±5%)	30W
Input Voltage	AC 220-240V
Power Factor	0.9
Surge Protection	3750V
Driver Type	Constant Driver

Optic Information	
LED Type	COB
Luminous Flux (±10%)	2550LM
Efficacy	85LM/W
Correlated Color Temperature	3000K/4500K/6500K
Color Rendering Index	Ra80
Beam Angle	110

Description

1. Wide available input voltage: AC:220-240V, suitable for most countries.
2. Pure aluminum housing for good heat dissipation and safe.
3. Energy saving, compared to traditional fluorescent lamp on the condition of same illumination, save up to 70%~80%.
4. Low noise, no UV and infrared radiation, a safe cold-light source.
5. Super long life, ten times to traditional energy-saving lamp.
6. Easy installation and conventional use.

Dimensions and Mount	
Product Dimension	Φ220*55MM
Export Carton Size	47.5*32.5*47.5CM
Material	Aluminum+Glass
Finish	Plating
Fixture Color	White+Black
IP Rating	IP20
Warranty	3 Years

Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features

** Please consult us for details.*