



Description

1. Wide available input voltage: AC:220-240V, suitable for most countries.
2. Pure aluminum housing for good heat dissipation and safe.
3. Energy saving, compared to traditional fluorescent lamp on the condition of same illumination, save up to 70%~80%.
4. Low noise, no UV and infrared radiation, a safe cold-light source.
5. Super long life, ten times to traditional energy-saving lamp.
6. Easy installation and conventional use.

Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

Electrical Information

| | | | |
|------------------------|-----------------|--|---|
| Model No. | SL-DL7001-15W | | |
| Power Consumption(±5%) | 15W | | |
| Input Voltage | AC 220-240V | | |
| Power Factor | 0.9 | | |
| Surge Protection | 3750V | | / |
| Driver Type | Constant Driver | | |

Optic Information

| | |
|------------------------------|-------------------|
| LED Type | COB |
| Luminous Flux (±10%) | 1275LM |
| Efficacy | 85LM/W |
| Correlated Color Temperature | 3000K/4500K/6500K |
| Color Rendering Index | Ra80 |
| Beam Angle | 111 |

Dimensions and Mount

| | |
|--------------------|----------------|
| Product Dimension | Φ160*50MM |
| Export Carton Size | 53*32.5*36CM |
| Material | Aluminum+Glass |
| Finish | Plating |
| Fixture Color | White+Black |
| IP Rating | IP20 |
| Warranty | 3 Years |

New Features

** Please consult us for details.*