



Electrical Information	
Model No.	AL-NX-DL7W
Power Consumption(±5%)	7W
Input Voltage	AC 220-240V
Power Factor	0.9
Surge Protection	3750V
Driver Type	Constent Driver

Optic Information	
LED Type	SMD
Luminous Flux (±10%)	490LM
Efficacy	70LM/W
Correlated Color Temperature	3000K/4500K/6500K
Color Rendering Index	Ra80
Beam Angle	105

Description

1. Wide available input voltage: AC:220-240V, suitable for most countries.
2. Pure aluminum housing for good heat dissipation and safe.
3. Energy saving, compared to traditional fluorescent lamp on the condition of same illumination, save up to 70%~80%.
4. Low noise, no UV and infrared radiation, a safe cold-light source.
5. Super long life, ten times to traditional energy-saving lamp.
6. Easy installation and conventional use.

Dimintions and Mount

Product Dimension	Φ100*40MM
Export Carton Size	54.5*39.5*25.5CM
Material	Aluminum+Acrylic
Finish	Plating
Fixture Color	White
IP Rating	IP20
Warranty	2 Years

Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features

** Please consult us for details.*