



Electrical Information				
Model No.	C102-9W	C102-12W	C102-18W	
Power Consumption(±5%)	9W	12W	18W	
Power Supply				
Input Voltage	AC 220-240V			
Power Factor	>0.90			
Surge Protection	3750V			/
Driver Type	Constant Driver			

Optic Information				
LED Type	LED 2835			
Luminous Flux (±10%)	630LM	840LM	1260LM	
Efficacy(4500K Ra70)	70LM/W			
Correlated Color Temperature	4500K			
Color Rendering Index	Ra80			
Beam Angle	70			

Description

1. Die-cast aluminum shell, excellent heat dissipation material, reduce the weakening of lamp beads.
2. High brightness SMD ChipLED source, high light transmittance, low light attenuation.
3. The die-cast aluminum casing and the heat dissipation area of the lamp reach 70%, which effectively protects the lamp bead from weakening.
4. SPRING BUCKLE: Can withstand 5 KG power to ensure firm installation.
5. Compared with non-isolated drivers, isolated drivers have no risk of electric shock and better protect the luminaire.

Dimensions and Mount

Product Dimension	φ93mm	φ112mm	φ163mm
Export Carton Size	L65.5*W35.5*H31mm	L55*W35.5*H35mm	L43*W42*H39mm
Gross Weight	8.9±0.3kg	11.8±0.3kg	15.1±0.3kg
Material	Aluminum		
	PC		
Finish	Powder Coating		
Fixture Color	Black White		
IP Rating	IP20		
Warranty	5 Years		

Applications

- used indoors, bedrooms, cabinets, kitchens, living rooms, cabinets, toilets, etc.

New Features

** Please consult us for details.*