

DATA SHEET - SL-MG02-DL18W LED DOWN LIGHT

Version: 3.0







C	ϵ	CB	
		OD	\sim

Electrical Information				
SL-MG02-DL18W				
18W				
AC 220-240V				
0.9				
3750V				
Constent Driver				
	18W AC 220-240V 0.9 3750V	18W AC 220-240V 0.9 3750V	18W AC 220-240V 0.9 3750V	

Optic Information				
LED Type	SMD			
Luminous Flux (±10%)	1260LM			
Efficacy	70LM/W			
Correlated Color Temperature	3000K/4500K/6500K			
Color Rendering Index	Ra80			
Beam Angle	80			

Dimentions and Mount			
Product Dimension	Ф175*40ММ		
Export Carton Size	56.5*23*41CM		
Material	Aluminum+PC		
materiai			
Finish	Plating		
Fixture Color	White		
IP Rating	IP20		
Warranty	3 Years		

Description

- 1.Wide available input voltage: AC:220-240V, suitable for most countries.
- 2. Pure aluminum housing for good heat dissipation and safe.
- 3. Energy saving, compared to traditional fluorescent lamp on the condition of sameillumination, save up to 70%~80%.
- 4.Low noise, no UV and infrared radiation, a safe
- cold-light source.

 5.Super long life, ten times to traditional energy-savinglamp.
 6.Easy installation and conventional use.

Applications

• Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features

* Please consult us for details.