



Electrical Information				
<b>Model No.</b>	PT-C2369SMD-7W	PT-C2369SMD-12W	PT-C2369SMD-20W	PT-C2369SMD-30W
<b>Power Consumption(±5%)</b>	7W	12W	20W	30W
<b>Input Voltage</b>	AC 100-240V	AC 100-240V	AC 100-240V	AC 100-240V
<b>Power Factor</b>	0.6	0.6	0.6	0.6
<b>Surge Protection</b>	3000V	3000V	3000V	3000V
<b>Driver Type</b>	Constant Driver	Constant Driver	Constant Driver	Constant Driver

Optic Information				
<b>LED Type</b>	COB	COB	COB	COB
<b>Luminous Flux (±10%)</b>	486.36LM	780LM	1438LM	2494LM
<b>Efficacy</b>	69.48LM/W	65LM/W	71.9LM/W	83.13LM/W
<b>Correlated Color Temperature</b>	3000K/4000K	6000K	3000K/6000K	6000K
<b>Color Rendering Index</b>	Ra80	Ra80	Ra80	Ra80
<b>Beam Angle</b>	60	60	60	60

### Description

1. Wide available input voltage: AC:100-240V, suitable for most countries.
2. Pure aluminum housing for good heat dissipation and safe.
3. Energy saving, compared to traditional fluorescent lamp on the condition of same illumination, save up to 70%~80%.
4. Low noise, no UV and infrared radiation, a safe cold-light source.
5. Super long life, ten times to traditional energy-saving lamp.
6. Easy installation and conventional use.

### Dimensions and Mount

<b>Product Dimension</b>	90*50MM	130*70MM	165*90MM	225*100MM
<b>Export Carton Size</b>	110*70*95MM	145*80*135MM	185*100*170MM	235*110*230MM
<b>Material</b>	Aluminum+PC	Aluminum+PC	Aluminum+PC	Aluminum+PC
<b>Finish</b>	Plating	Plating	Plating	Plating
<b>Fixture Color</b>	White+Gray	White+Gray	White+Gray	White+Gray
<b>IP Rating</b>	IP20	IP20	IP20	IP20
<b>Warranty</b>	3 Years	3 Years	3 Years	3 Years

### Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

### New Features

\* Please consult us for details.