



Electrical Information			
Model No.	5341-3 (COB)	5341-3 (CREE)	
Power Consumption(±5%)	14W	14W	
Input Voltage	AC 220-240V	AC 220-240V	
Power Factor	0.6	0.6	
Surge Protection	1500V	1500V	
Driver Type	Constant Driver	Constant Driver	

Optic Information			
LED Type	LED 2835	LED 2835	
Luminous Flux (±10%)	980LM	980LM	
Efficacy	70LM/W	70LM/W	
Correlated Color Temperature	WW / WH / RGB	WW / WH / RGB	
Color Rendering Index	Ra80	Ra80	
Beam Angle	/	/	

Description

- 1.Exquisite aluminium material makes lamp body structure, firm and durable,showingmore.IP54 waterproof rating, Exceptional waterproof performance.
- 2.Thick material durable safe and reliable grade.
- 3.High power LED lamp beads, high brightness, low light decay,long lasting and durable.

Dimintions and Mount

Product Dimension	230*230*60MM	230*230*60MM	
Color Box Size	/	/	
Material	Aluminium+PC	Aluminium+PC	
Finish	Powder Coating	Powder Coating	
Fixture Color	BK	BK	
IP Rating	IP54	IP54	
Warranty	2 Years	2 Years	

Applications

- Home,hotel,stadiums,villas, garden, balcony, aisle, corridor, room, external wall, gate, aisle,corridor, courtyard, etc.

New Features

** Please consult us for details.*