



Electrical Information			
Item No.	CX20-FG330L	CX20-FG600L	
Power Consumption(±5%)	18W	30W	
Power Supply	/	/	
Input Voltage	AC 100-240V	AC 100-240V	
Power Factor	0.9	0.9	
Surge Protection	/	/	/
Driver Type	Constant Driver	Constant Driver	

Optic Information			
LED Type	SMD	SMD	
Luminous Flux (±10%)	1296LM	2494LM	
Efficacy	72Lm/W	83.13Lm/W	
Correlated Color Temperature	3000K/6500K	3000K/6500K	
Color Rendering Index	Ra80	Ra80	
Beam Angle	120	120	

### Description

1. High aesthetic value, widely used magnetic ceiling light, minimalist style
2. High safety, no risk of electric shock when installing or replacing lighting fixtures or directly touching the track with hands.
3. Easy to install and maintain, just lay the track in advance, and the lighting fixtures can be sucked in in just one second.
4. Powerful lighting function, high flexibility, all magnetic lamps are on the track, without the need for multiple open or hidden wires, and can be equipped with different lighting fixtures.

### Dimensions and Mount

Product Dimension	320*22*43mm	600*22*43mm	
Export Carton Size	39*35*29cm	62*39*23.6cm	
Gross Weight	/	/	
Material	Aluminum+PC	Aluminum+PC	
Finish	Plating	Plating	
Fixture Color	BK	BK	
IP Rating	IP20	IP20	
Warranty	2 Years	2 Years	

### Applications

- Residential buildings, hotels, sports venues, villas, gardens, balconies, corridors, bedrooms, living rooms, corridors, rooms, gates, corridors, courtyards, etc.

### New Features

*\* Please consult us for details.*