



## Description

1. Adopting an internal and external strong earthquake resistant structure design, it effectively solves problems such as bulb detachment, shortened bulb life, and bracket fracture caused by strong vibrations.
2. Using high-efficiency gas discharge lamps as light sources, the bulb has a lifespan of over 10000 hours, making it particularly suitable for outdoor large-scale unmanned lighting.
3. It has good electromagnetic compatibility and will not cause electromagnetic interference to the surrounding environment.
4. The overall heat dissipation of the lamp is good, which can reduce the probability of failure.

## Applications

- LED flood lights are mainly used for individual buildings, exterior wall lighting of historical building clusters, internal and external transparent lighting of buildings, indoor local lighting, green landscape lighting, billboard lighting, medical and cultural facilities lighting, and atmosphere lighting of entertainment places such as bars and dance halls.

## Electrical Information

Model No.	SL-XWN-FL300W			
Power Consumption(±5%)	300W			
Input Voltage	AC 220-240V			
Power Factor	0.9			
Surge Protection				/
Driver Type	Constant Driver			

## Optic Information

LED Type	SMD
Luminous Flux (±10%)	24000LM
Efficacy	80LM/W
Correlated Color Temperature	3000K/4500K/6500K
Color Rendering Index	Ra80
Beam Angle	90

## Dimensions and Mount

Product Dimension	395*60*340MM		
Export Carton Size	41*32.5*36CM		
Material	Aluminum+Glass		
Finish	Plating		
Fixture Color	Gray		
IP Rating	IP65		
Warranty	3 Years		

## New Features

*\* Please consult us for details.*