



| Electrical Information | | | |
|-------------------------|------------|--------------|---|
| Model No. | H800-2 SQ | H800-2 SQ-CH | |
| Application | MR16 / COB | MR16 / COB | |
| Input Voltage | / | | |
| Power Factor | / | | |
| Surge Protection | / | | / |
| Driver Type | / | | |

| Dimensions and Mount | | | |
|---------------------------|-------------------|-------------------|--|
| Product Dimension | 185*100*37mm | 185*100*37mm | |
| Export Carton Size | 59.5 X 27 X 41CM | 59.5 X 27 X 41CM | |
| Cutout | 170*90mm | 170*90mm | |
| Material | Die-casting AL+PC | Die-casting AL+PC | |
| Finish | Plating | Plating | |
| Fixture Color | SN+UV BK Chrome | SN+UV Chrome | |
| IP Rating | / | | |
| Warranty | 2 Years | 2 Years | |
| | | | |
| | | | |
| | | | |
| | | | |

Description

1. The lamp body is made of aluminum alloy, and the reflector is made of plastic
2. Fix the bulb firmly & Easy installation
3. Optional reflector colors, Adjustable angle.
4. Our downlight housing is suitable for Dia.50mm MR16/GU10 bulbs/Halogen Bulb.
5. Cut a hole in the ceiling and the sturdy spring loaded wings hold it in place, with spring clips will self-adjust to various wall thickness.
6. Installation method: Recessed.

Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features

** Please consult us for details.*