



Electrical Information	
Model No.	MZ-141
Power Consumption(±5%)	7W
Input Voltage	AC 220-240V
Power Factor	0.9
Surge Protection	3000V
Driver Type	Constant Driver

Optic Information	
LED Type	COB
Luminous Flux (±10%)	490LM
Efficacy	70LM/W
Correlated Color Temperature	3000K
Color Rendering Index	Ra90
Beam Angle	20

Description
<ol style="list-style-type: none"> 1. Wide available input voltage: AC:220-240V, suitable for most countries. 2. Pure aluminum housing for good heat dissipation and safe. 3. Energy saving, compared to traditional fluorescent lamp on the condition of same illumination, save up to 70%~80%. 4. Low noise, no UV and infrared radiation, a safe cold-light source. 5. Super long life, ten times to traditional energy-saving lamp. 6. Easy installation and conventional use.

Dimensions and Mount	
Product Dimension	85*85*100MM
Export Carton Size	70*43*30CM
Material	Aluminum+PC
Finish	Plating
Fixture Color	BK
IP Rating	IP20
Warranty	3 Years

Applications
<ul style="list-style-type: none"> • Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features
<p><i>* Please consult us for details.</i></p>