



Electrical Information			
Model No.	GX53-1	GX53-2	GX53-3
Power Consumption(±5%)	7W	7W	7W
Input Voltage	AC 220-240V	AC 220-240V	AC 220-240V
Power Factor	0.55	0.55	0.55
Surge Protection	3000V	3000V	3000V
Driver Type	Constant Driver	Constant Driver	Constant Driver

Optic Information			
LED Type	SMD	COB	SMD
Luminous Flux (±10%)	490LM	490LM	490LM
Efficacy	70LM/W	70LM/W	70LM/W
Correlated Color Temperature	3000K	3000K	3000K
Color Rendering Index	Ra80	Ra90	Ra90
Beam Angle	120	20	24

Description

1. Wide available input voltage: AC:220-240V, suitable for most countries.
2. Pure aluminum housing for good heat dissipation and safe.
3. Energy saving, compared to traditional fluorescent lamp on the condition of same illumination, save up to 70%~80%.
4. Low noise, no UV and infrared radiation, a safe cold-light source.
5. Super long life, ten times to traditional energy-saving lamp.
6. Easy installation and conventional use.

Dimensions and Mount

Product Dimension	77*30MM	77*30MM	77*30MM
Export Carton Size	42.5*34*28CM	42.5*34*28CM	42.5*34*28CM
Material	Aluminum+PC	Aluminum+PC	Aluminum+PC
Finish	Plating	Plating	Plating
Fixture Color	BK	BK	BK
IP Rating	IP20	IP20	IP20
Warranty	3 Years	3 Years	3 Years

Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features

* Please consult us for details.