

DATA SHEET - HF-A1182 LED TRACK LIGHT

Version: 3.0





and no harmful substances such as mercury



Electrical Information	
Item No.	HF-A1182
Power Consumption(±5%)	25W
Input Voltage	AC 220-240V
Power Factor	0.9
Surge Protection	1500V /
Driver Type	Constent Driver

Optic Information	
LED Type	SMD
Luminous Flux (±10%)	2000LM
Efficacy	80Lm/W
Correlated Color Temperature	3000K
Color Rendering Index	Ra80
Beam Angle	24

Dimentions and Mount		
Product Dimension	78*135mm	
Export Carton Size	185*80*170mm	
Gross Weight	/	
Material	Aluminum+PC	
Finish	Plating	
Fixture Color	WH/BK	
IP Rating	IP20	
Warranty	2 Years	

4. The deep hidden anti glare design of the light source can create a

high-end and durable

Description

comfortable lighting environment 5. The track lamp is equipped with a high conversion rate drive for

3. The track light is made of high-quality aluminum material, which is

cross flow, ensuring the performance and lifespan of the lamp

1. Using LED as the light source, its characteristics are low heat generation, no radiation, and no heavy metal pollution 2. The color is purer than other lamps, with high luminous efficiency

Applications

• Residential buildings, hotels, sports venues, villas, gardens, balconies, corridors, bedrooms, living rooms, corridors, rooms, gates, corridors, courtyards, etc.

New Features

* Please consult us for details.