

DATA SHEET - HF-A1180-4 LED TRACK LIGHT

Version: 3.0





| CE | СВ | | LED Type | SMD |
|----|----|--|------------------------------|--------|
| | | | Luminous Flux (±10%) | 1275LM |
| | | | Efficacy | 85Lm/W |
| | | | Correlated Color Temperature | 3000K |
| | | | Color Rendering Index | Ra80 |
| | | | Beam Angle | 24 |

Optic Information

Description

- 1. Using LED as the light source, its characteristics are low heat generation, no radiation, and no heavy metal pollution

 2. The color is purer than other lamps, with high luminous efficiency
- and no harmful substances such as mercury
- 3. The track light is made of high-quality aluminum material, which is high-end and durable
- 4. The deep hidden anti glare design of the light source can create a comfortable lighting environment
- 5. The track lamp is equipped with a high conversion rate drive for cross flow, ensuring the performance and lifespan of the lamp

| Dimentions and Mount | | | | |
|----------------------|--------------|--|--|--|
| Product Dimension | 82*82*163mm | | | |
| Export Carton Size | 160*55*160mm | | | |
| Gross Weight | / | | | |
| Material | Aluminum+PC | | | |
| Material | | | | |
| Finish | Plating | | | |
| Fixture Color | WH/BK | | | |
| IP Rating | IP20 | | | |
| Warranty | 2 Years | | | |

Applications

• Residential buildings, hotels, sports venues, villas, gardens, balconies, corridors, bedrooms, living rooms, corridors, rooms, gates, corridors, courtyards, etc.

New Features

^{*} Please consult us for details.