



Electrical Information			
Model No.	B1016-7W	B1016-18W	B1016-30W
Power Consumption(±5%)	7W	18W	30W
Input Voltage	AC 220-240V	AC 220-240V	AC 220-240V
Power Factor	0.5	0.5	0.5
Surge Protection	1500V	1500V	1500V
Driver Type	/	/	/

Optic Information			
LED Type	COB	COB	COB
Luminous Flux (±10%)	490LM	1260LM	2100LM
Efficacy	70LM/W	70LM/W	70LM/W
Correlated Color Temperature	3000K/4500K/6500K	3000K/4500K/6500K	3000K/4500K/6500K
Color Rendering Index	Ra80	Ra80	Ra80
Beam Angle	80	95	90

Description

- 1.Wide available input voltage: AC:220-240V, suitable for most countries.
- 2.The material has good heat dissipation and is safe and reliable.
- 3.Energy saving,compared to traditional fluorescent lamp on the condition of sameillumination, save up to 70%~80%.
- 4.Low noise, no UV and infrared radiation, a safe cold-light source.
- 5.Super long life, ten times to traditional energy-savinglamp.
- 6.Easy installation and conventional use.

Dimentions and Mount

Product Dimension	Φ95*H42MM	Φ160*H50MM	Φ230*H62MM
Color Box Size	52.5*51*22.5CM	54.5*31.5*37CM	48.5*35*48.5CM
Material	Iron+PC	Iron+PC	Iron+PC
Finish	Plating	Plating	Plating
Fixture Color	White/Black	White/Black	White/Black
IP Rating	IP20	IP20	IP20
Warranty	3 Years	3 Years	3 Years

Applications

- Office building, corridor, balcony, bedroom, study, Stairs, living room, exhibition stand, hallway

New Features

** Please consult us for details.*