



Electrical Information				
Model No.	C102-9W	C102-12W	C102-18W	C102-40W
Power Consumption(±5%)	9W	12W	18W	40W
Power Supply				
Input Voltage	AC 220-240V			
Power Factor	>0.90			
Surge Protection	3750V			
Driver Type	Constant Driver			

Optic Information				
LED Type	LED 2835			
Luminous Flux (±10%)	630LM	840LM	1260LM	3000LM
Efficacy(4500K Ra70)	70LM/W			
Correlated Color Temperature	4500K			
Color Rendering Index	Ra80			
Beam Angle	70			

Description

1. Die-cast aluminum shell, excellent heat dissipation material, reduce the weakening of lamp beads.
2. High brightness COB ChipLED source, high light transmittance, low light attenuation.
3. The die-cast aluminum casing and the heat dissipation area of the lamp reach 70%, which effectively protects the lamp bead from weakening.
4. SPRING BUCKLE: Can withstand 5 KG power to ensure firm installation.
5. Compared with non-isolated drivers, isolated drivers have no risk of electric shock and better protect the luminaire.

Dimensions and Mount

Product Dimension	φ93mm	φ112mm	φ163mm	φ225mm
Export Carton Size	L57.5*W30*H23mm	L55*W34*H34mm	L42*W34*H34mm	L57.5*W50*H24mm
Gross Weight	8.9±0.3kg	11.8±0.3kg	15.1±0.3kg	24±0.3kg
Material	Aluminum PC			
Finish	Powder Coating			
Fixture Color	Black White			
IP Rating	IP20			
Warranty	5 Years			

Applications

- used indoors, bedrooms, cabinets, kitchens, living rooms, cabinets, toilets, etc.

New Features

* Please consult us for details.