



Electrical Information			
Model No.	CL-UGL-6W	CL-UGL-12W	
Power Consumption(±5%)	6W	12W	
Input Voltage	AC 220-240V	AC 220-240V	
Power Factor	0.9	0.9	
Surge Protection	3000V	3000V	
Driver Type	Constant Driver	Constant Driver	

Optic Information			
LED Type	OSRAM 3030	OSRAM 3030	
Luminous Flux (±10%)	510LM	900LM	
Efficacy	85LM/W	75LM/W	
Correlated Color Temperature	3000K	3000K	
Color Rendering Index	Ra80	Ra80	
Beam Angle	15	15	

Description

1. Efficient light source;
2. High quality aluminum material, beautiful appearance, and reasonable structure;
3. Tempered glass as cover, heat-resistant and impact-resistant;
4. Waterproof IP65 for outdoor use;

Dimensions and Mount

Product Dimension	Φ120*H90MM	Φ180*H90MM	
Export Carton Size	52*26.5*39.5CM	38.5*31.5*38.5CM	
Material	Aluminum+Plastic+Glass	Aluminum+Plastic+Glass	
Finish	Plating	Plating	
Fixture Color	Silver+Black	Silver+Black	
IP Rating	IP65	IP65	
Warranty	2 Years	2 Years	

Applications

- The elegant products for outdoor decoration lighting, which could be widely used for outdoor squares, parks, public places of entertainment, inground, underground, brick pave, concrete floor as decoration and lighting as well.

New Features

** Please consult us for details.*