



Electrical Information			
Item No.	CX26-FG300	CX26-FG600	
Power Consumption(±5%)	10W	20W	
Power Supply	/	/	
Input Voltage	DC 48V	DC 48V	
Power Factor	0.9	0.9	
Surge Protection	/	/	/
Driver Type	Constant Driver	Constant Driver	

Optic Information			
LED Type	SMD	SMD	
Luminous Flux (±10%)	800LM	1600LM	
Efficacy	80Lm/W	80Lm/W	
Correlated Color Temperature	3000K	3000K	
Color Rendering Index	Ra80	Ra80	
Beam Angle	120	120	

Description

1. High aesthetic value, widely used magnetic ceiling light, minimalist style
2. High safety, no risk of electric shock when installing or replacing lighting fixtures or directly touching the track with hands.
3. Easy to install and maintain, just lay the track in advance, and the lighting fixtures can be sucked in in just one second.
4. Powerful lighting function, high flexibility, all magnetic lamps are on the track, without the need for multiple open or hidden wires, and can be equipped with different lighting fixtures.

Dimensions and Mount

Product Dimension	304*26*25mm	600*26*25mm	
Export Carton Size	32.8*18.5*32cm	62.7*18.5*32cm	
Gross Weight	/	/	
Material	Aluminum+PC	Aluminum+PC	
Finish	Plating	Plating	
Fixture Color	BK	BK	
IP Rating	IP20	IP20	
Warranty	2 Years	2 Years	

Applications

- Residential buildings, hotels, sports venues, villas, gardens, balconies, corridors, bedrooms, living rooms, corridors, rooms, gates, corridors, courtyards, etc.

New Features

** Please consult us for details.*